

product specifications for:

Marine Grade Wire & Cable

Item #: Various

Description

Ancor™ Marine Grade Primary Wire & Battery Cable

Electrical Specifications

Max. Voltage: 600V

Material Specifications

Jacket: PVC

Jacket Rating: TEW 600V

105°C (221°F) Dry

75°C (167°F) Wet

Strands: Tinned stranded copper

Standards and Certifications

UL Listed: E67078 (UL1426)

CSA Listed: 022035_0_000

ABYC: Yes

US Coast Guard: Title 33, Part 183.435



18-4/0 AWG Wire and Cable Specifications

Wire Size	Nominal O.D.	Wire Diameter	Minimum Bend Radius	Stranding No. of 30 AWG	Cir. Mil Area	Ohms per 1000'	mm ²	Wt. per 1000'				
18 AWG	.08 mm ²	7/64"	2.8 mm	1.0 mm	7/8"	2.3 cm	16	1600	6.48	.08	12 lbs	5.4 kg
16 AWG	1 mm ²	1/8"	3.2 mm	1.5 mm	31/32"	2.5 cm	26	2600	4.00	1.31	16 lbs	7.3 kg
14 AWG	2 mm ²	9/64"	3.6 mm	2.0 mm	1-3/32"	2.8 cm	41	4100	2.53	2.08	23 lbs	10.4 kg
12 AWG	3 mm ²	5/32"	4.0 mm	2.6 mm	1-1/4"	3.2 cm	65	6500	1.75	3.31	31 lbs	14 kg
10 AWG	5 mm ²	7/32"	5.6 mm	3.3 mm	1-29/64"	3.7 cm	105	10,500	1.00	5.26	44 lbs	20 kg
8 AWG	8 mm ²	5/16"	7.9 mm	4.3 mm	2-1/32"	5.2 cm	168	16,800	0.62	8.37	86 lbs	39 kg
6 AWG	13 mm ²	11/32"	8.7 mm	5.5 mm	2-35/64"	6.5 cm	266	26,600	0.40	13.30	118 lbs	53.5 kg
4 AWG	21 mm ²	13/32"	10.3 mm	7.0 mm	3-3/32"	7.9 cm	420	42,000	0.24	21.15	178 lbs	81 kg
2 AWG	34 mm ²	15/32"	11.9 mm	8.0 mm	3-1/2"	8.9 cm	665	66,500	0.16	33.62	277 lbs	126 kg
1 AWG	42 mm ²	17/32"	13.5 mm	9.0 mm	4-9/64"	10.4 cm	836	83,690	0.13	42.38	350 lbs	159 kg
1/0 AWG	53 mm ²	9/16"	14.3 mm	10.5 mm	4-1/2"	11.4 cm	1064	105,600	0.10	53.49	437 lbs	198 kg
2/0 AWG	68 mm ²	5/8"	15.9 mm	12.0 mm	4-59/64"	12.4 cm	1330	133,000	0.08	67.43	549 lbs	249 kg
3/0 AWG	85 mm ²	11/16"	17.5 mm	13.0 mm	5-23/64"	13.7 cm	1665	167,800	0.06	85.01	675 lbs	306 kg
4/0 AWG	107 mm ²	13/16"	20.6 mm	14.0 mm	5-7/8"	15.0 cm	2109	211,600	0.05	107.20	837 lbs	380 kg